



# Rotary laser Digi Roto HVR

ROTARY LASERS



4 HANDLES FOR EASY CARRYING AND PROTECTION

METAL HEAD

LASER PLUMB (ZENITH)

DIGITAL SLOPE IN X AND Y-AXIS

DUST AND WATER PROTECTION IP67



WITH REMOTE CONTROL AND DIGITAL RECEIVER

LASER PLUMB (NADIR)



ADJUSTMENT OF ROTATION SPEED AND SCANNING SECTOR VIA ROTO REMOTE APP

2+1\* WARRANTY YEAR



## TECHNICAL CHARACTERISTICS

Working range with receiver	600 m
Accuracy	0,09 mm/m
Self-levelling	± 5°
Rotation speed	0, 60, 120, 300, 600 rpm
Scanning mode	0°, 10°, 45°, 90°, 180°
Dust and water protection	IP67
Laser type	Class II, 635 nm < 1 mW
Power supply	4 x 1,2 V 4000 mAh Ni-MH rechargeable battery
Dimensions	206x206x211 mm
Weight	3 kg

**Roto Remote App** enables you to control the laser via Bluetooth from your smartphone. Main functions:

- display of the battery charge level
- mode selection
- rotation speed measurement
- adjustment of a scanning sector
- manual adjustment of the tilt angle



## DELIVERY PACKAGE

### Digi Roto HVR

Item nr.	7-2-096
Laser Digi Roto HVR	•
Ni-MH batteries	•
Laser receiver X-act Roto	•
Charger	•
Remote control	•
Universal mount	•
Mount for laser receiver	•
Laser glasses	•
Magnetic target	•
Plastic case	•

