



Rotary laser Roto HVR

ROTARY LASERS



2+1* WARRANTY YEAR



TECHNICAL CHARACTERISTICS

Working range with receiver	600 m
Accuracy	0,09 mm/m
Self-levelling	± 5°
Rotation speed	0, 60, 120, 300, 600 rpm
Scanning mode	0°, 10°, 45°, 90°, 180°
Dust and water protection	IP67
Laser type	Class II, 635 nm < 1 mW
Power supply	4 x 1,2 V 4000 mAh Ni-MH rechargeable battery
Dimensions	206x206x211 mm
Weight	2,5 kg

Roto Remote App enables you to control the laser via Bluetooth from your smartphone. Main functions:

- display of the battery charge level
- mode selection
- rotation speed measurement
- adjustment of a scanning sector
- manual adjustment of the tilt angle



DELIVERY PACKAGE	Roto HVR	Roto HVR Set
Item nr.	7-2-000	7-2-094
Laser	•	•
Ni-MH batteries	•	•
Laser receiver X-act Roto	•	•
Charger	•	•
Universal mount	•	•
Mount for laser receiver	•	•
Laser glasses	•	•
Magnetic target	•	•
Geodatic tripod Geo	•	•
Leveling pole Flexi Staff	•	•
Plastic case	•	•

